


止逆閥 Check Valves



規格說明 SPECIFICATIONS

附屬品 ATTACHMENT

型式 MODLE		最高使用壓力 MAX. OPERATED PRESSURE (bar)	啟流壓力 CRACKING PRESSURE (bar)	定格流量 RATED FLOW (l/min)	重量 WEIGHT (kg)	
CV-03G-※	CV-03T-※	210	05 : 0.5 50 : 5	40	0.2	1.7
CV-04T-※				60	0.4	
CV-06G-※	CV-06T-※			100	0.7	4.2
CV-08T-※				180	1	
CV-10G-※	CV-10T-※			350	2.1	7.8
CV-12T-※				600	3.2	

型式 MODLE	安裝螺絲 SOC HOL CAP SCREW
CV-03G	M10 X 45L.....4pcs
CV-06	M16 X 55L.....4pcs
CV-10G	M20 X 65L.....4pcs

型號說明 HOW TO ORDER

CV - 03 G - 05

啟流壓力 CRACKING PRESSURE
05 : 0.5 bar 50 : 5 bar

接續型式 TYPE OF CONNECTION
G : 座墊型 SUB-PLATED TYPE
T : 配管型 THREAD TYPE

閥口徑 VALVE SIZE
03 : 3/8" 04 : 1/2" 06 : 3/4" 08 : 1"
10 : 1-1/4" 12 : 1-1/2"

系列編號 SERIES NUMBER