

Measurement Unlimited by The Imagination.

Non-contacting Radar Level Gauge

KRG-10



intelligent
DIGITAL
LEVEL GAUGE

Features

1. ±2mm High Accuracy

TOKYO KEIKI's advanced pulse technologies achieve ±2mm accuracy.

2. Advanced Echo Processing

"Multi-echo Historical-validation" checks trend continuity to track the echoes from liquid during process operation for smooth measurement. And, "Auto Noise Table Function" is achieves stable and continuous level measurement on the Reactor tank application.

3. Rapid Tracking

"Full-range Search Mode" boosts detection speed and track up to 2m/sec level change.

4. Flow & Volume Calculation

"Extended Calculation Mode" outputs not only Tank Volume, but also Open Channel Flow Rate by Weir & Flume combination.

5. Wide line-up for various applications

KRG-10 can be installed for Corrosive, Adhesive and Hygienic applications by various antenna; Standard Cone, PTFE-Sealing and PFA-Rod. 4" down to even 1" tank nozzle can be applicable.

Specifications

General Specification	Frequency	26GHz	
	Beam Angle	8° (4inch Cone antenna & PTFE Sealing antenna)	
		18°(2inch Cone antenna & PTFE Sealing antenna) 25°(1inch Rod antenna)	
Measurement	MAX range	30m	
	Accuracy	Cone & PTFE Sealing	±2mm
		Rod	±3mm
	Repeatability	±1mm	
	Interval	1s	
Tracking rate	2m / sec max.		
Display	5 digits LCD / 4 keys-menu-driven Level, Distance, Volume (Flow), Current, Signal strength selectable		
Power Supply Signal Output	Power Supply (Loop-Powered)	DC10.5V ~ 36V (In case of Ex, the voltage is rated separately.)	
	Signal Output	4 ~ 20mA + HART	
	Alarm	Hold, 22mA or 3.6mA selectable	
	Ambient Temperature	-40 ~ + 70°C (Non-Ex) / -40 ~ + 60°C (Ex)	
Mechanical Specification	Tank Pressure	1.5MPa	
	Tank Temperature	-40 ~ + 200°C	
	IP Class	IP66, NEMA4X	
	ATEX	II 1G Ex ia IIC T4 Ga / II 1D Ex ia IIIC T135°C Da, IP66 II 1/2G Ex d ia IIC T4 Gb/Ga / II 2G Ex d ia IIC T4 Gb, IP66	
	IECEX	Ex ia IIC T4 Ga / Ex ia IIIC T135°C Da, IP66 Ex d ia IIC T4 Gb/Ga / Ex d ia IIC T4 Gb, IP66	
Function	- Multi-echo historical validation - Bottom echo handler - Volume calculation	- Disturbance noise elimination - Double bounce handler - Predict Output	- Distance filter window - Full-range search mode - Flow rate calculation (Weir / Flume)

Design and specifications are subject to change without prior notice, and without any obligation on the part of the manufacturer.




TOKYO KEIKI INC.

Measurement Systems Company

Head Office

2-16-46, Minami-Kamata, Ohta-ku, Tokyo 144-8551 JAPAN TEL. +81-3-3737-8664 FAX. +81-3-3737-8665

www.tokyo-keiki.co.jp/ryutai/